MediaMAX™

Premise Distribution System
RF Splitter Modules

SAM-RF3

SAM-RF4


SAM-RF6


SAM-RF8


SAM-RFH3


SAM-RFH4

SAM-RFH6

SAM-RFH8

Specifications

Frequency Range: 5 - 2400MHz
RFI Shielding: 130dB
Operating Temperature: -40°F to 140°F
"F" Ports: Meet ANSI/SCTE 02 2006

Dimensions:
SAM-RF3: 3.0" H x 6.5" W x 2.0" D
All others: 2.75" H x 6.5" W x 2.8" D

Description

Suttle MediaMAX™ video splitter modules provide high quality and reliable video distribution with industry approved, digital ready splitters that meet ANSI/SCTE standards.

The angled mounting brackets maximize enclosure space, minimize cable strain, and facilitate better cable management and ease of installation.

	RF3	RF4	RF6	RF8	RFH3	RFH4	RFH6	RFH8
Insertion Loss (max)	7.0dB	8.0dB	11.8dB	12dB	11.2dB	12.5dB	14.5dB	15dB
Isolation (min)	22dB	22dB	22dB	20dB	22dB	20dB	22dB	20dB
Return Loss In (min)	20dB	20dB	20dB	20dB	12dB	12dB	13dB	13dB
Return Loss Out (min)	20dB	20dB	20dB	20dB	11dB	12dB	13dB	12dB

Product Information

Suttle Part Number	Description
SAM-RF3	1 x 3 RF splitter - 1GHz
SAM-RF4	1 x 4 RF splitter - 1GHz
SAM-RF6	1 x 6 RF splitter - 1GHz
SAM-RF8	1 x 8 RF splitter - 1GHz

Suttle Part Number	Description
SAM-RFH3	1 x 3 RF splitter - 3GHz
SAM-RFH4	1 x 4 RF splitter - 3GHz
SAM-RFH6	1 x 6 RF splitter - 3GHz
SAM-RFH8	1 x 8 RF splitter - 3GHz

Specifications subject to change without notice. Copyright 2017. 3540417

1001 East Highway 212 • Hector, MN USA 55342 • **suttlesolutions.com**
Toll Free: 1 (800) 852-8662 • Local: (320) 848-6711 • Fax: (320) 848-6218